

tesa® Powerstrips Waterproof Duo Hook metal-plastic



Product Information

BNR 59785

Product Description

Ш

Product Features

- · Easy to mount without drilling, screws or nails
- · Strong hold up to 3kg
- Removable without a trace due to the Powerstrips Waterproof technology
- · Material combination stainless steel & plastic
- Usable on tiles, glass, etc. in humid rooms or directly in the shower*
- Especially developed for wet areas (e.g. shower, bath tub etc.)
- · Ideal to hold e.g. a sponge, washrag, etc. if needed in the shower
- · Reusable with tesa Powerstrips Waterproof Large

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materiall

- · Easy to mount without drilling, screws or nails
- Strong hold up to 3kg
- Removable without a trace due to the Powerstrips Waterproof technology
- Material combination stainless steel & plastic
- Usable on tiles, glass, etc. in humid rooms or directly in the shower*
- Especially developed for wet areas (e.g. shower, bath tub etc.)
- Ideal to hold e.g. a sponge, washrag, etc. if needed in the shower
- · Reusable with tesa Powerstrips Waterproof Large

Application Fields

||

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Type of adhesive synthetic rubber
Hook shape Rectangular

Holding power up to
3 Kg

^{*}Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material



tesa® Powerstrips Waterproof Duo Hook metal-plastic

Product Information

Properties/Performance Values

•	Application temperature from	+15 °C	•	Ozone resistance	no
•	Application temperature to	+35 °C	•	Residue free removal	yes
•	Applicationfield	Bathroom, Kitchen	•	Reusable	yes
•	Chemical resistance	no	•	Reusable with	Powerstrips
•	Hazard material	yes			Waterproof Large
•	Material	Stainless steel, Plastic	•	Solvent free	yes
•	Oil and grease resistance	no	•	Temperature resistance	yes
			•	UV-resistant	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.