



tesapack[®] express

Product Information

BNR 57804, 57810

Product Description

tesapack[®] Express is a self-adhesive packaging tape equipped with easy-tear edges. It can simply be torn by hand without the help of scissors or a dispenser.

Product Features

- Very strong PP backing with easy-tear edges
- Solvent-free adhesive with high UV-resistance
- Convenient and fast sealing without utilities
- Excellent transparency for neat packaging
- Even, low-noise unwinding

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing material | BOPP and PVC | • Total thickness | 60 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------------|-----------------------|-----------|
| • Elongation at break | 20 % | • Low noise unwinding | yes |
| • Tensile strength | 13 N/cm | • Solvent free | yes |
| • Adhesive strength | High adhesion | • Suitable surfaces | Cardboard |
| • Ageing resistance (UV) | yes | • Tear resistance | yes |
| • Hand tearability | yes | • Unwind force n/cm | 3 N/cm |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>