



# tesa® 4440

## Product Information

Painter's tape for professional paint jobs outdoors

### Product Description

The precision painter's tape tesa® 4440 consists of a particularly tearproof, flat Washi special base which is fitted with an UV-stable adhesive made from acrylate. Since the base material has been additionally waterproofed, the painter's tape can be used outdoors for up to 26 weeks for challenging paint work, including on slightly rough surfaces. Here, it allows creating particularly precise, sharp and clean paint edges. The high-quality painter's tape is easy to work with, can be torn off by hand and be removed from the surface without any residue – even after several weeks. With only one taping off process, several paint coats can be applied, thus allowing professional painters to save time and money. Furthermore, it is compatible with all commercially available paints, lacquers and glazes and can also be used for light plastering work.

### Product Features

- Professional paint jobs outdoors (up to 26 weeks)
- Light plasterwork tasks
- Ideal for sharp paint edges
- Also suitable for rough surfaces

\*The application of an adhesive tape on weathered surfaces may lead to residues during the de-masking. Thus before using an adhesive tape on a weathered surface we recommend to make a trial application for up to 24 hours.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |             |                   |        |
|--------------------|-------------|-------------------|--------|
| • Backing material | Washi paper | • Total thickness | 110 µm |
|--------------------|-------------|-------------------|--------|

### Properties/Performance Values

- |                       |     |                    |           |
|-----------------------|-----|--------------------|-----------|
| • Elongation at break | 5 % | • Hand tearability | very good |
|-----------------------|-----|--------------------|-----------|

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?mp=04440>