



tesa® Professional 4844

Product Information

Premium Plastering tape Embossed, labelled

Product Description

tesa® 4840 has especially been developed to protect precious and sensitive surfaces against dirt and damage during all kinds of painting and plastering work. It consists of a stable, ribbed film backing which is coated with an uv-resistant natural rubber based adhesive. The cross-grooves allow you to tear the tape off easily and cleanly at a perfect 90° angle. This allows the plastering tape to be used quickly and precisely - at all corners and right angles. This plastering tape comprises a sturdy film backing which is coated with a light- and aging-resistant natural rubber adhesive compound.

Application Fields

- Outdoor applications
- Protection of smooth and delicate surfaces during plastering and painting
- Suitable for applications above 5°C
- Long-term applications (up to 6 weeks)

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Total thickness 140 µm

Properties/Performance Values

- Tensile strength 22 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04844>