

tesa® extra Power Perfect

Product Information

BNR 56343, 56341, 56342, 56344, 56339

Product Description

tesa cloth tape extra Power Perfect is a premium quality repair tape designed for demanding indoor and outdoor applications.

Product Features

- Cloth tape for all professional solutions like handicrafts, fastening, bundling, strengthening, marking and much more
- Very strong adhesive power, even on rough and oily surfaces
- For permanent high resilience and long-term results
- Weather-resistant cloth tape for in-and outdoor applications
- Tear-resistant but tearable by hand
- Can be written on
- Available in a wide range of colours

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing materialType of adhesive	Acrylic-coated cloth natural rubber	Total thickness	310 μm
Properties/Performance Values			
 Tensile strength Adhesive strength Ageing resistance (UV) Application temperature from Application temperature to Area of use Hand tearability Humidity resistance Oil and grease resistance Ozone resistance Residue free removal 	100 N/cm Very high adhesion yes +10 °C +50 °C In- and Outdoor yes yes yes yes yes	 Solvent free Suitable surfaces Tear resistance Temperature resistance max Tensibility UV-resistant Water resistance Waterproof Writable 	yes Even wood, Tiles, Brick, Most plastics, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone yes yes 140 °C 13 % yes yes yes yes



tesa® extra Power Perfect

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 24/07/25 – en-GB