

tesa® PRO 66714 Mounting Slim

Product Information

tesa PRO Mounting Slim - Strong and thin tape - Ideal for indoor uses for various surfaces - Double-sided adhesive - Only 9 mm wide - $5 \text{ m} \times 9 \text{ mm}$

Product Description

tesa PRO Mounting Slim

Fix objects that are slimmer than a regular tape without using nails or screws with tesa PRO Mounting Slim. The extra thin, double-sided tape is only 9 mm wide. Achieve a clean mounting job on indoor surfaces with this strong and durable tape. It is suitable for indoor use and holds onto surfaces like tiles, painted wood, veneer, steel (most metals), most plastic and glass. No form of mounting work is quicker or easier than taping.

Apply in vertical strips and along the full length of the object or surface. Press down firmly on the mounting tape for at least five seconds.

Product Features

*To use, where a regular tape is too wide: This durable and resistant tape is only 9 mm wide - for fast and easy mounting without damaging the wall structure with screws, plugs or nails

*Ideal for interior use: Strong double-sided adhesive tape for secure fixing of flat objects such as signs and more

*Easy to use: The mounting tape can be cut into individual small or large pieces for an adhesive strip in the optimized size

Application Fields

Easy to apply:

- In order for the mounting tape to develop its full holding power, the object and surface must be free of dust, dirt and grease.
- Don't touch the open adhesive surface as it could impair the adhesive strength.
- Press down firmly on the mounting tape for at least five seconds.
- For removal, carefully pull the mounting tape parallel from the wall.
- As the mounting tapes are intended for permanent use, material residues may remain on the object. Try to remove with tesa adhesive remover.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material PE foam • Total thickness 1000 μm

Type of adhesive tackified acrylic



tesa® PRO 66714 Mounting Slim

Product Information

Properties/Performance Values

Tensile strength

Ageing resistance (UV)

10 N/cm very good Humidity resistance

very good

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

