



tesa® Professional 60399

Product Information

tesa® 60399 Plastering Tape

Product Description

tesa® 60399 is a plasticized PVC tape with low unwinding force and medium adhesion with a flat film.

Having a rubber adhesive coating, tesa® 60399 is suitable for most surfaces.

Once applied, the tape can withstand humidity, weak alkaline solutions, acids and many other chemicals.

Product Features

- Sturdy masking tape with powerful adhesive performance that sticks even to slightly rough surfaces
- Versatile applications, from masking over bundling to fixation
- Weather-resistant tape that provides UV protection for two weeks
- Residue-free for 14 days
- Good handling qualities, such as stretching to 170% during application
- Ready for use in temperatures from +5 °C to +60°C
- A choice of orange or white tapes
- Tape composition: backing material = sPVC, adhesive = natural rubber
- Available sizes: 33m:30mm, 33m:50mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing material | PVC film | • Total thickness | 130 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------|------|
| • Elongation at break | 170 % | • Hand tearability | good |
| • Tensile strength | 20 N/cm | • Humidity resistance | good |
| • Easy to remove | yes | | |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 2 N/cm |
|---------|--------|



tesa® Professional 60399

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=60399>