

tesa® Professional 74921

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PE film	• Total thickness	35 µm
• Type of adhesive	water-based acrylic		

Properties/Performance Values

• Elongation at break	200 %	• Material of masking coverage	LDPE
• Tensile strength	5.5 N/cm	• Residue free removal	yes
• Application temperature from	-5 °C	• Residue-free removable after...	90 days
• Application temperature to	60 °C	days	
• Backing weight	29 g/m ²	• Suitable for rough surfaces	no
• Easy to remove	yes	• Suitable for sensitive surfaces	yes
• Humidity resistance	good	• Tear resistance	no
• Material	LDPE (Low-density polyethylene)	• Water resistance	medium

Adhesion to Values

• steel	0.8 N/cm
---------	----------

Storage Conditions

Storage Conditions

tesa® Self-adhesive Protection Film - Glass should be stored away from sunlight, humidity between 10% and 70%, temperature between 5°C and 30°C.

tesa® Professional 74921

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=74921>