

tesa[®] 4423

Product Information

Paper Stencil Material for Short Term Sandblasting Applications

Product Description

This tape is suitable for almost all painting applications during construction or renovation of ships and boats. It is suitable for a variety of common surfaces such as glass, aluminium, wood and especially hard-PVC.

Product Features

- Durability during sandblasting applications 6 sec./4 bar
- Flatback paper backing with good plottability, paint anchorage, hand tearability and resistance to temperatures up to 60°C
- Good adhesion to various surfaces, clean removal

Application Fields

Closing and reinforcing of shipping cartons

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing material | flat paper | • Total thickness | 145 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 5 % | • Hand tearability | very good |
| • Tensile strength | 57 N/cm | • Temperature resistance (60 min) | 60 °C |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 4.5 N/cm |
|---------|----------|

tesa® 4423

Product Information

Additional Information

The unique features of tesa® 4423 offer further benefits: *Can be peeled off easily *Pliable and easy to cut by hand *Will not distort when used for long straight lines (e.g. for masking of water lines in boat building or multi-colour painting of narrow stripes)

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4423>