

tesa® Ultra Power underwater repair tape

Product Information

BNR 56491

Product Description

Waterproof Repair Tape – Built for tough outdoor fixes, even on wet surfaces. This durable tape provides strong adhesion for sealing leaks, patching holes, and repairing cracks. It's easy to apply and holds up in extreme weather thanks to its high resistance to UV rays and temperature changes. Ideal for adventurers, gardeners, and anyone tackling outdoor repairs.

Product Features

- Fixes damage even underwater – perfect for wet surface repairs
- Extra thick and rubberised for strong, reliable adhesion
- Highly resistant to weather and UV – ideal for outdoor use
- Flexible and easy to apply – conforms to any shape or object
- Works on dry and wet surfaces – seals holes, cracks, gaps, and tears
- Special-purpose tape – suitable for sealing drainage and other tricky repairs

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------|-------------------|--------|
| • Backing material | Caotchouc | • Total thickness | 660 µm |
| • Type of adhesive | butyl rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------------|--------------------|--------------------------|------------------------------------|
| • Tensile strength | 33 N/cm | • Residue free removal | no |
| • Abrasion resistance | yes | • Solvent free | no |
| • Adhesive strength | Very high adhesion | • Suitable surfaces | Most plastics, Glass, Metal, Steel |
| • Ageing resistance (UV) | yes | | |
| • Area of use | In- and Outdoor | • Tear resistance | yes |
| • Hand tearability | no | • Temperature resistance | yes |
| • Oil and grease resistance | yes | • UV-resistant | yes |
| • Ozone resistance | yes | • Waterproof | yes |
| | | • Writable | no |

tesa® Ultra Power underwater repair tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4641DIY>