

tesa® Adjustable Adhesive Nail for Wallpaper & Plaster 2kg



Product Information

BNR 77777

Product Description

Height adjustable Adhesive Nail for up to 2kg. Ideal for hanging and aligning pictures on textured and sensitive surfaces like wallpaper or plaster. Height adjustable Adhesive Nail for up to 2kg. Ideal for hanging and aligning pictures on textured and sensitive surfaces like wallpaper or plaster.

Product Features

- For textured and sensitive surfaces like wallpaper or plaster
- For objects up to 2kg* per nail or 4kg using 2 nails
- Height adjustable for straight alignment
- Removable without a trace
- Reusable with a new strip

*For optimal results please read instruction leaflet

- For textured and sensitive surfaces like wallpaper or plaster
- For objects up to 2kg* per nail or 4kg using 2 nails
- Height adjustable for straight alignment
- Removable without a trace
- Reusable with a new strip

*For optimal results please read instruction leaflet

Application Fields

How to Apply – Step by Step:

- Clean the surface with a dust-free cloth to remove any dirt or dust.
- Apply the Adhesive Strip to the rougher surface (e.g. wallpaper or plaster), with the blue tab facing the wall. Ensure the surface can support the weight of the item.
- Press down evenly across the entire strip for at least 5 seconds, then remove the protective foil. This activates the flexible polymer chains that form strong U-shaped bonds with the surface.
- Align the tesa® Adjustable Adhesive Nail with the top edge of the strip, fold it down, and press evenly for at least 5 seconds.
- Leave the tab accessible behind your object or below the nail for easy removal.
- Push the red toggle up to unlock the nail head, adjust it to the desired position, then push the toggle back down until it clicks to lock it in place.

tesa® Adjustable Adhesive Nail for Wallpaper & Plaster 2kg

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|--------------------------------|------|
| • Type of adhesive | synthetic rubber | • Holding power of strip up to | 2 Kg |
|--------------------|------------------|--------------------------------|------|

Properties/Performance Values

- | | | | |
|--------------------------------|------------------|------------------------|-----|
| • Application temperature from | -15 °C | • Ozone resistance | no |
| • Chemical resistance | no | • Residue free removal | yes |
| • Hazard material | no | • Reusable | yes |
| • Humidity resistance | no | • UV-resistant | no |
| • Material | PS (polystyrene) | • Waterproof | no |
| • Oil and grease resistance | no | | |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=77777>