

tesa® 64283

Product Information



tesa® 64283EU General Purpose Strapping Tape

Product Description

tesa® 64283 is a general purpose strapping tape designed with a high-performance tensilized polypropylene backing and rubber adhesive system. This advanced formulation ensures exceptional initial tack on both polar and non-polar surfaces, making it the preferred choice across diverse applications and industries. The mono-oriented polypropylene backing showcases outstanding tensile strength and minimal elongation, ensuring utmost durability and reliability. With effortless dispensing, our tape accommodates both manual and automatic operations.

Product Features

- solvent-free adhesive
- low elongation
- good workability

Application Fields

- Holding of appliance parts
- Holding and securing of peripherals
- Residue-free removability from a variety of different surfaces without discoloration
- High conformability to different shapes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|-------|
| • Backing material | MOPP | • Total thickness | 80 µm |
| • Type of adhesive | synthetic rubber | • Colour | blue |

Product Assortment

- | | |
|--------------------|------------|
| • Available colors | light blue |
|--------------------|------------|

Properties/Performance Values

- | | | | |
|-----------------------|----------|------------------------|-----|
| • Elongation at break | 35 % | • No discolouration | yes |
| • Tensile strength | 190 N/cm | • Residue free removal | yes |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 6 N/cm |
|---------|--------|

tesa® 64283

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64283EU>