

tesa® Professional 4939

Product Information

Double-sided removable carpet tape

Product Description

tesa® Professional 4939 is a double-sided removable carpet tape that was developed specially for temporary use. It consists of a fabric substrate and a synthetic-rubber adhesive mass. The removable carpet tape forms a strong bond with carpets and rugs, but a weaker one with the surface underneath. It can be removed easily within 14 days without leaving residue. It is very easy to handle as it can be torn by hand. The universal removable carpet tape is a useful aid anywhere that (red) carpets are only needed for a short period.

Product Features

- Temporary textile floor coverings
- Can be used on many surfaces (except natural and synthetic stone)
- Ideal for fairs, exhibitions, conventions & renovations
- Especially for screed, mastic and epoxy-sealed floors

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Backing material | cloth | • Total thickness | 250 µm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------|------|
| • Elongation at break | 40 % | • Hand tearability | low |
| • Tensile strength | 50 N/cm | • Humidity resistance | good |
| • Chemical resistance | good | | |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 5.5 N/cm |
|---------|----------|

tesa® Professional 4939

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4939PRO>