

# tesa® Powerstrips Waterproof Duo Hook metal-plastic



## Product Information

BNR 59785

## Product Description

Double Hook – Self-Adhesive Stainless Steel & Plastic, Waterproof for Shower Installation

## Product Features

- Easy to mount without drilling, screws or nails
- Strong hold up to 3kg
- Removable without a trace due to the Powerstrips Waterproof technology
- Material combination - stainless steel & plastic
- Usable on tiles, glass, etc. in humid rooms or directly in the shower\*
- Especially developed for wet areas (e.g. shower, bath tub etc.)
- Ideal to hold e.g. a sponge, washrag, etc. if needed in the shower
- Reusable with tesa Powerstrips Waterproof Large

\*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

- Easy to mount without drilling, screws or nails
- Strong hold up to 3kg
- Removable without a trace due to the Powerstrips Waterproof technology
- Material combination - stainless steel & plastic
- Usable on tiles, glass, etc. in humid rooms or directly in the shower\*
- Especially developed for wet areas (e.g. shower, bath tub etc.)
- Ideal to hold e.g. a sponge, washrag, etc. if needed in the shower
- Reusable with tesa Powerstrips Waterproof Large

\*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

## Application Fields

How to Apply:

- Clean the surface with alcohol or a silicone-free glass cleaner.
- Use the included waterproof primer tissue to wipe over the surface. Wait at least 10 seconds.
- Apply the Powerstrip Waterproof Large strips to the surface and press firmly for at least 5 seconds.
- Detach the hook's base plate and stick it onto the strips. Press firmly for at least 5 seconds.
- Slide the hook down onto the base plate until it locks into place.

# tesa® Powerstrips Waterproof Duo

## Hook metal-plastic

### Product Information

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                       |                  |              |             |
|-----------------------|------------------|--------------|-------------|
| • Type of adhesive    | synthetic rubber | • Hook shape | Rectangular |
| • Holding power up to | 3 Kg             |              |             |

### Properties/Performance Values

- |                                |                          |                          |                  |
|--------------------------------|--------------------------|--------------------------|------------------|
| • Application temperature from | +15 °C                   | • Ozone resistance       | no               |
| • Application temperature to   | +35 °C                   | • Residue free removal   | yes              |
| • Applicationfield             | Bathroom, Kitchen        | • Reusable               | yes              |
| • Chemical resistance          | no                       | • Reusable with          | Powerstrips      |
| • Hazard material              | yes                      |                          | Waterproof Large |
| • Material                     | Stainless steel, Plastic | • Solvent free           | yes              |
| • Oil and grease resistance    | no                       | • Temperature resistance | yes              |
|                                |                          | • UV-resistant           | no               |

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=59785>