

tesapack® Bio & Strong

Product Information



BNR 58296

Product Description

tesapack® BIO & STRONG is a more sustainable, high-tack packing tape. With strong adhesion for parcels up to 20kg and a transparent film made from renewable raw materials, it's a reliable all-rounder for eco-conscious packaging.

Product Features

tesapack bio & strong: The transparent PLA tape is environmentally friendly and ideal for packaging and bonding heavy boxes up to 20 kg

High performance packaging tape: The tape offers extra strong adhesive strength and is free from solvents due to the use of water-based natural rubber adhesive

PLA as backing material: tesapack Bio & Strong parcel tape is almost exclusively made from highly sustainable materials (98%) and lower carbon

footprint compared to other fossil-based carton sealing tapes

Powerful and uncomplicated: The adhesive tape is a reliable alternative to fossil based plastic adhesive tapes and is suitable for manual or automatic parcel tape dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	Poly lactide (PLA)	• Total thickness	50 µm
• Type of adhesive	water-based acrylic		

Properties/Performance Values

• Tensile strength	31.2 N/cm	• Low noise unwinding	no
• Adhesive strength	Very high adhesion	• Solvent free	yes
• Ageing resistance (UV)	no	• Suitable surfaces	Cardboard, Paper
• Hand tearability	no	• Tear resistance	yes

Certificates

Certified according to
Din Certco

For latest information on this product please visit <http://l.tesa.com/?cp=60400PLA30>

tesapack® Bio & Strong

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=60400PLA30>