

tesa[®] PRO

Product Information

BNR 66462

Product Description

The tesa PRO STRONG duct tape 66462 is a versatile, more sustainable solution for all types of repairs. It provides strong bonding, water resistance, and easy tearability for both indoor and outdoor use all while containing more than 60% post-consumer recycled materials in its backing.

Product Features

- tesa PRO STRONG Duct Tape for professionals of every craft, your general purpose tape that is easy to apply and works even on slightly rough surfaces.
- PRO STRONG Duct Tape is truly reliable for various applications like sealing, repairing, fastening or packaging.
- Backing made from more than 60% post-consumer recycled materials - increasing sustainability and reducing waste!
- Based on synthetic rubber, this new PRO STRONG Duct Tape has never been stronger while still being easy to unwind and convenient to tear. Use indoors or outdoors.
- A must-have for every craftsmen toolbox: The tesa PRO STRONG Duct Tape is for temporary and permanent applications, the perfect all round support with superior tesa quality.

Application Fields

This Duct Tape works best on clean, smooth surfaces. Apply the tape and press firmly onto the surface.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|---|--------------------|--------------------|------------------|
| • Backing material | PE laminated cloth | • Type of adhesive | synthetic rubber |
| • Bio-based carbon content of liner (acc. DIN EN 16640) | 67 % | • Total thickness | 230 µm |

Properties/Performance Values

- | | | | |
|--------------------------|---------------|------------------------|------|
| • Elongation at break | 16 % | • Hand tearability | good |
| • Tensile strength | 41.2 N/cm | • Humidity resistance | yes |
| • Abrasion resistance | very good | • Residue free removal | no |
| • Adhesive strength | High adhesion | • Solvent free | yes |
| • Ageing resistance (UV) | yes | • Tear resistance | yes |
| • Chemical resistance | yes | • Writable | yes |

tesa® PRO

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=60462PRO>