

tesa® Professional Permanent

Product Information



60021, 60020

Product Description

tesa Spray Glue Permanent is a spray adhesive for large surfaces. It offers extra strong bonding for typical household materials such as paper or cardboard.

Product Features

- For clean, economical, secure and fast bonding of large areas
- Suitable for light and medium-weight materials with slightly uneven surfaces
- Finely and evenly dispersion of glue
- Fast drying
- Resistant to damp and temperature from -20°C up to +60°C
- Suitable for Styrofoam®
- Free from silicone

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Silicone free	yes
-----------------	-----

Properties/Performance Values

• Adhesive strength	Light adhesion	• Solvent free	no
• Chemical resistance	yes	• Suitable for children of 3 years of age	no
• Compostable	no	• Suitable surfaces	Even wood, Brick, Acrylic glass, Stone
• Hazard material	yes	• Temperature resistance	yes
• Humidity resistance	yes	• Temperature resistance max	60 °C
• Minimum temperature resistance	-20 °C	• UV-resistant	yes
• Recommended distance of spraying	30 cm	• Washable	no
• Residue free removal	no	• Waterproof	yes

tesa® Professional Permanent

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=60020>