

tesapack® Paper Standard ecoLogo

Product Information



BNR 58293, 58292, 58291

Product Description

tesapack Paper Standard - Eco-friendly paper packaging tape, 56% bio-based material - Effective and easy to recycle - Brown - 50 m x 50 mm

Product Features

- tesapack Paper Standard: This environmentally friendly paper adhesive tape is ideal for packaging and sealing light to medium-weight cardboard up to 10 kg
- Extremely versatile: The parcel tape offers strong adhesion on smooth and rough surfaces and is suitable for manual or automatic packaging tape dispensers
- Sustainable: tesa Paper Standard packing tape is made with paper from well-managed, FSC®-certified forests and other controlled sources (FSC® C148769) and can be disposed together with the cardboard box
- Durable paper for a secure seal: The adhesive tape is humidity-resistant - at the same time, it can be torn off by hand and is easy to unroll

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing material | Paper | • Total thickness | 125 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------|-------------------|-----------------------|------------------|
| • Elongation at break | 10 % | • Low noise unwinding | yes |
| • Tensile strength | 33 N/cm | • Solvent free | yes |
| • Adhesive strength | Standard adhesion | • Suitable surfaces | Cardboard, Paper |
| • Ageing resistance (UV) | no | • Tear resistance | no |
| • Hand tearability | yes | • Unwind force n/cm | 3 N/cm |

Certificates

Certified according to
FSC® C148769

tesapack® Paper Standard ecoLogo

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4713PAP10>