

# tesa® 4174

## Product Information



Fine line tape for design painting

### Product Description

tesa® 4174 is an extra-skinning tape with a PVC substrate and a natural rubber adhesive mass. The fine line tape, which resists temperatures of up to 150 °C, is suitable for covering sharp edges and is a valuable aid when carrying out paint jobs on cars and motorbikes. Due to the high degree of stretchiness, painters can tackle challenging jobs with ease, e.g. painting bumpers. This special adhesive tape can be torn by hand, is easy to handle and can be removed quickly after use.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing material | PVC film       | • Total thickness | 110 µm |
| • Type of adhesive | natural rubber |                   |        |

### Properties/Performance Values

- |                    |           |                                   |                |
|--------------------|-----------|-----------------------------------|----------------|
| • Tensile strength | 25 N/cm   | • Suitable for die cutting        | yes            |
| • Easy to remove   | yes       | • Temperature resistance (30 min) | not applicable |
| • Hand tearability | very good |                                   |                |

### Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 3.7 N/cm |
|---------|----------|

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4174>