

tesafilm® CRYSTAL RECYCLED

Product Information



59032, 59034, 59035, 59036, 59047, 59040, 59048, 59044, 59043

Product Description

tesafilm® CRYSTAL RECYCLED is a highly transparent, tear-resistant adhesive tape suitable for a wide range of uses. The backing film is made from 90% post-consumer recycled plastic (PCR PET), with the total tape containing 64% recycled content (excluding core and packaging). A sustainable choice without compromising on quality.

Sustainable Aspects

- Tape backing: 90% post-consumer recycled plastic (PCR PET). Total tape contains 64% recycled content (excluding core and packaging). Claim validated by UL to UL 2809#2 (ECVP Environmental Claim Validation Procedure).
- INGEDE Method 12 certified: does not hinder the recycling of paper and cardboard.

Product Features

- Sustainable Contribution: Backing made from 90% post-consumer recycled plastic (PCR PET); total tape contains 64% recycled content (excluding core and packaging). Validated by UL to UL2809-2 Environmental Claim Validation Procedure.
- Clear Quality: Fully transparent with strong adhesive power – almost invisible on many surfaces.
- High Performance: Tear-resistant and long-lasting adhesive strength.
- Quiet Unwind: Unrolls smoothly and silently for low-noise use.
- Easy to Use: Compatible with all tesa® dispensers.
- INGEDE-12 Certified: Safe for paper and cardboard recycling – does not interfere with the recycling process.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing material | PET film | • Total thickness | 44 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|---------------------|------------------|
| • Elongation at break | 100 % | • Photocopy neutral | yes |
| • Tensile strength | 43 N/cm | • Solvent free | yes |
| • Ageing resistance (UV) | yes | • Suitable surfaces | Cardboard, Paper |
| • Hand tearability | no | • Tear resistance | yes |
| • Low noise unwinding | yes | • Transparency | good |
| • Material | PCR PET | • Unwind force n/cm | 3 N/cm |

tesafilm® CRYSTAL RECYCLED

Product Information

Certificates

Certified according to

- INGEDE12
- UL ECVP 2809-2 (validity: 2023-08-25 to 2026-08-25, region(s): Offenburg, Germany)

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=59032A>