

tesa® Professional 74922

Product Information

Sustainable Aspects

tesa® Self-adhesive Protection Paper is made with paper from well-managed FSC®-certified forests, recycled materials, and other controlled sources and it meets the FSC® Standards.

The communication of the FSC® certification is strictly limited to sales organisations that are FSC® certified (FSC® C148769).

Product Features

- Easy application to protect against dirt, dust, and paint splashes even on the most sensitive surfaces
- Easy removal without leaving any residues for up to 3 months
- Repositionable multiple times
- Fully coated for enhanced durability and performance
- Smooth and thick craft paper that prevents paint bleed through

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------------|-------------------|--------|
| • Paper | Recycled content of backing | • Total thickness | 140 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------------|---------------------|-----------------------------------|---------|
| • Elongation at break | 1 % | • Residue free removal | yes |
| • Tensile strength | 50 N/cm | • Residue-free removable after... | 90 days |
| • Application temperature from | 5 °C | • Solvent free | yes |
| • Application temperature to | 60 °C | • Suitable for rough surfaces | no |
| • Backing weight | 90 g/m ² | • Suitable for sensitive surfaces | yes |
| • Easy to remove | yes | • Tear resistance | no |
| • Humidity resistance | low | • UV resistance indoor | 4 weeks |
| • Material | Paper | • Water resistance | no |
| • Material of masking coverage | paper | | |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 0.4 N/cm |
|---------|----------|

tesa® Professional 74922

Product Information

Certificates

Sustainability Certificates

FSC® Certified

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=74922>