

tesa® Insulation Double#Sided Door Seal



Product Information

5418

Product Description

tesa® Insulation Double#Sided Door Seal protects against draughts, dust and noise. Quick, tool#free fitting with no drilling or glue. Ideal for under#door gaps up to 22 mm. Removes cleanly without residue.

Product Features

- Suitable for smooth, flat floors
- Perfect for under#door gaps up to 22 mm
- Stops draughts, dust, cold, heat, noise and insects
- Installs in seconds – no drilling or gluing
- Simply slide under the door leaf
- Double door bottom seal available in grey and white

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Gap coverage up to 22 mm

Properties/Performance Values

- | | | | |
|------------------------|---|---------------------|---------------|
| • Chemical resistance | no | • Reusable | yes |
| • Material | Polyester, PE (polyethylene), LDPE (Low-density polyethylene) | • Solvent free | yes |
| | | • Suitable surfaces | Wooden floors |
| • Residue free removal | yes | | |

tesa[®] Insulation Double#Sided Door Seal

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5418A>