

tesa® INSULATION Weatherstrip Silicone – One Size Fits All



Product Information

5417

Product Description

tesa® INSULATION Weatherstrip PREMIUM sealing tape helps draught#proof your home against cold, heat, and noise. Robust material with strong adhesive lasts up to 15 years. Ideal for windows and doors. UV# and temperature#resistant.

Product Features

- Improved home comfort with effective draught#proof gap sealing
- Flexible silicone seal for 1–7 mm gaps – fits most window and door frames
- Self#adhesive for quick, tool#free installation
- Long#lasting performance: up to 15 years
- Outstanding resistance to weather, UV, and ozone
- High temperature tolerance: –50 °C to +60 °C
- Airtight and watertight barrier
- Transparent finish
- Easy to wipe clean

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|----------------------|------|
| • Backing material | Fabric | • Gap coverage up to | 7 mm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|----------------------------------|----------|------------------------------|-------|
| • Chemical resistance | no | • Residue free removal | no |
| • Durability | 15 years | • Solvent free | yes |
| • Material | Silicone | • Temperature resistance | yes |
| • Minimum temperature resistance | –20 °C | • Temperature resistance max | 60 °C |

tesa® INSULATION Weatherstrip Silicone – One Size Fits All

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5417A>