

tesa® INSULATION Weatherstrip Rubber L



Product Information

5391, 5390, 55703, 5395

Product Description

The tesa® INSULATION Weatherstrip helps keep your home comfortable by blocking draughts, heat loss, noise and moisture. Simple to fit, UV and temperature resistant. Reliably seals gaps in windows and doors 2–5 mm wide.

Product Features

- Enhanced home comfort through gap sealing
- Suitable for large gaps (L) from 2–5 mm
- Effective insulation against cold, heat, noise and moisture
- Quick, easy self-adhesive installation
- Durability: up to 8 years
- Removes cleanly
- High UV and ozone resistance
- Temperature resistant from –50 °C to +60 °C

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|----------------------|------|
| • Backing material | EPDM rubber foam | • Gap coverage up to | 5 mm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|----------------------------------|-----------|------------------------------|-------|
| • Chemical resistance | no | • Residue free removal | no |
| • Durability | 8 years | • Solvent free | yes |
| • Humidity resistance | yes | • Temperature resistance | yes |
| • Material | Synthetic | • Temperature resistance max | 60 °C |
| • Minimum temperature resistance | –20 °C | | |

tesa® INSULATION Weatherstrip Rubber L

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5390A>