

tesa® INSULATION Weatherstrip Rubber XL



Product Information

55706, 5389, 5393

Product Description

The tesa® INSULATION Weatherstrip made of rubber protects your home from cold, heat, noise and moisture. Easy to install, it seals windows and doors effectively. Ideal for gaps from 3 to 7 mm.

Product Features

- Improve home comfort with effective draught#proof gap sealing
- Fits very large gaps (XL) from 3–7 mm
- Insulates against cold, heat, noise, and moisture
- Quick, easy installation with self#adhesive backing
- Long#lasting performance: up to 8 years
- Removes cleanly when needed
- Highly weather#resistant for year#round protection
- Temperature resistant from –50 °C to +60 °C

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|----------------------|------|
| • Backing material | EPDM rubber foam | • Gap coverage up to | 7 mm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|----------------------------------|-----------|------------------------------|-------|
| • Chemical resistance | no | • Residue free removal | no |
| • Durability | 8 years | • Solvent free | yes |
| • Humidity resistance | yes | • Temperature resistance | yes |
| • Material | Synthetic | • Temperature resistance max | 60 °C |
| • Minimum temperature resistance | –20 °C | | |

tesa® INSULATION Weatherstrip Rubber XL

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5393A>