

tesa® 61023

Product Information

75 µm PET tape for Electrical Insulation applications

Product Description

tesa® 61023 is a blue 75 µm PET tape with a water-based acrylic adhesive. tesa® 61023 PV2 has been designed for electrical insulation applications in EV batteries.

Product Features

- Dielectric breakdown and leakage current protection
- Anti-Repulsion performance
- Optimized for process automation and automated in-line detection
- Reworkability

Application Fields

- Cell-Wrapping
- Metal-Part Insulation

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PET	• Total thickness	75 µm
• Type of adhesive	water-based acrylic		

Properties/Performance Values

• Elongation at break	80 %	• CTI (adhesive side)	600 V
• Tensile strength	50 N/cm	• CTI (backing side)	400 V
• Breakdown voltage	7 KV	• Liner removal force	40 cN/cm

Adhesion to Values

• steel	5 N/cm
---------	--------

tesa® 61023

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=61023>