

# tesa® Professional 4453

## **Product Information**

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing material	Washi paper	•	Total thickness	73 µm
•	Type of adhesive	water-based acrylic			

# **Properties/Performance Values**

•	Elongation at break	10 %	•	Paint anchorage	very good
•	Tensile strength	31 N/cm	•	Residue free removal	yes
•	Area of use	In- and Outdoor	•	Sharp colour edge	very good
•	Easy to remove	yes	•	Solvent free	yes
•	Hand tearability	very good	•	Suitable for sensitive surfaces	good

#### Adhesion to Values

•	stee	1	Ν	I/cm	
---	------	---	---	------	--

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

