

tesa® 4224EUPV12

Product Information



tesa® 4224EU PV12 General Purpose Strapping Tape

Product Description

tesa® 4224EU PV12 is a general-purpose strapping tape with tensilized polypropylene backing and rubber adhesive to provide good initial tack. The mono-oriented polypropylene backing exhibits high conformability, good tensile strength, and low elongation. With effortless dispensing, our tape accommodates both manual and automatic operations.

Product Features

- Solvent-free adhesive & release
- High initial tack
- Low elongation
- Good conformability

Application Fields

- Lightweight bundling applications
- Holding of lightweight appliance parts
- Reinforcing and unitizing

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|-------|
| • Backing material | MOPP | • Total thickness | 85 µm |
| • Type of adhesive | synthetic rubber | • Colour | white |

Properties/Performance Values

- | | | | |
|-----------------------|----------|------------------------|-----|
| • Elongation at break | 35 % | • Residue free removal | yes |
| • Tensile strength | 190 N/cm | • Solvent free | yes |
| • No discolouration | yes | | |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 6 N/cm |
|---------|--------|

tesa® 4224EUPV12

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4224EUPV12>