# tesafilm® TRANSPARENT

## Product Information

57341, 57372, 57406, 57404, 57369, 57342, 57405, 57371, 57345, 57403, 57379, 57401, 57378, 57352, 57402

### Product Description

tesafilm® TRANSPARENT: An all-purpose adhesive tape for office, home and school use. Strong adhesion, high tear resistance, clear, glossy finish. Made from durable Polypropylene, solvent-free adhesive.

### Product Features

- Universal adhesive tape for office, home and school with strong adhesion and high tear resistance

Transparent design for discreet use on many materials and surfaces

Durable solution thanks to robust polypropylene plastic and solvent-free adhesive

Ageing-resistant film stays reliably sticky even after a long time

Pleasant handling thanks to silent unwinding of the tape

Compatible with tesafilm® dispensers for comfortable use at a desk or in hand

Solvent-free adhesive

Ideal for wrapping, securing, repairing or decorating in everyday use

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

| | | | |
|---|---|---|---|
| • Backing material | BOPP | • Total thickness | 48 µm |
| • Type of adhesive | water-based acrylic | | |

### Properties/Performance Values

| | | | |
|---|---|---|---|
| • Tensile strength | 25 N/cm | • Solvent free | yes |
| • Ageing resistance (UV) | yes | • Suitable surfaces | Cardboard, Paper |
| • Hand tearability | no | • Tear resistance | yes |
| • Low noise unwinding | yes | • Transparency | good |
| • Material | PP (polypropylene) | • Unwind force n/cm | 2.5 N/cm |
| • Photocopy neutral | yes | • Writable | no |

**For latest information on this product please visit http://l.tesa.com/?cp=4140A**

# tesafilm® TRANSPARENT

Product Information

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

**For latest information on this product please visit http://l.tesa.com/?cp=4140A**