

# tesapack®

## Product Information

58292, 58291, 58293

### Product Description

The tesapack® STANDARD PAPER is ideal for securely packaging light parcels. It's easy to unroll and can be torn by hand. With 56% renewable materials such as paper from well-managed, certified forests and other controlled sources, it contributes to sustainability.

### Product Features

- Good adhesive performance for reliable light parcel packaging
- Practical to use: Easily torn by hand and unrolls quietly
- Composed of 56% renewable materials including paper from well-managed, certified forests and other controlled sources
- Core is 100% recycled cardboard
- INGEDE-12 certified: tesapack® STANDARD PAPER does not harm the recycling process of paper and cardboard
- Works optimally with all tesapack® hand dispensers (Classic, Comfort, Economy or Premium)

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing material | Paper          | • Total thickness | 125 µm |
| • Type of adhesive | natural rubber |                   |        |

### Properties/Performance Values

- |                          |                   |                       |                  |
|--------------------------|-------------------|-----------------------|------------------|
| • Elongation at break    | 10 %              | • Low noise unwinding | yes              |
| • Tensile strength       | 33 N/cm           | • Solvent free        | yes              |
| • Adhesive strength      | Standard adhesion | • Suitable surfaces   | Cardboard, Paper |
| • Ageing resistance (UV) | no                | • Tear resistance     | no               |
| • Hand tearability       | yes               | • Unwind force n/cm   | 3 N/cm           |

### Certificates

#### Certified according to

- FSC® C148769
- INGEDE12

# tesapack®

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4713PAP10A>