

tesapack®

Product Information

56000

Product Description

The tesapack® ULTRA STRONG PAPER is perfect for securely packaging heavy parcels. It offers strong adhesive performance, high tear resistance, and unrolls quietly. Made from 52% renewable materials and such as paper from well-managed, certified forests and other controlled sources, it makes a contribution to sustainability.

Product Features

- Strong adhesive performance for reliable packaging of heavy parcels
- High-quality material with fiberglass filament for high tear resistance
- Even, quiet unrolling for comfortable use
- Made from 52% renewable materials, including paper from well-managed, certified forests and other controlled sources
- Core made from 100% recycled cardboard
- INGEDE-12 certified: tesapack® ULTRA STRONG PAPER does not harm the recycling process of paper and cardboard
- Optimal processing with all tesapack® hand dispensers (Classic, Comfort, Economy or Premium)

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	Glasfiber filament reinforced paper	• Total thickness	210 µm
• Type of adhesive	synthetic rubber		

Properties/Performance Values

• Elongation at break	6 %	• Low noise unwinding	yes
• Tensile strength	125 N/cm	• Solvent free	yes
• Adhesive strength	Very high adhesion	• Suitable surfaces	Cardboard, Paper
• Ageing resistance (UV)	no	• Tear resistance	yes
• Hand tearability	no	• Unwind force n/cm	1 N/cm

Certificates

Certified according to

- INGEDE12

tesapack®

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=60013PAP30A>