

tesafilm® CLEAR RECYCLED

Product Information

57035, 57046, 57043, 56997, 57049, 57074, 57070

Product Description

The tesafilm® CLEAR RECYCLED adhesive tape is crystal#clear, tear#resistant and versatile. The backing of this high#quality tape is made from 100% post#industrial recycled plastic.

Sustainable Aspects

- Tape (backing): 100% post-industrial recycled plastic - certified by DIN CERTCO (Registration number: 8Y0002), a certification company of the TÜV Rheinland Group

Product Features

- Sustainable choice: Backing made from 100% post#industrial recycled plastic – certified by DIN CERTCO (Registration number: 8Y0002), part of the TÜV Rheinland Group
- Crystal#clear: Transparent with strong adhesion – near#invisible on many surfaces
- High performance: Tear#resistant film that keeps its grip over time
- Quiet unwinding: Detaches smoothly and quietly from the roll
- Easy to use: Compatible with tesafilm® dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing material | BOPP | • Total thickness | 52 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|---------------------|------------------|
| • Elongation at break | 20 % | • Solvent free | yes |
| • Tensile strength | 50 N/cm | • Suitable surfaces | Cardboard, Paper |
| • Ageing resistance (UV) | yes | • Tear resistance | no |
| • Hand tearability | no | • Transparency | good |
| • Low noise unwinding | yes | • Unwind force n/cm | 2.6 N/cm |
| • Photocopy neutral | yes | • Writable | no |

Certificates

Certified according to

- Din Certco

tesafilm[®] CLEAR RECYCLED

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4112A>