

# tesa® 4328

## Product Information



Red colored premium masking tape for various applications

### Product Description

tesa® 4328 is a red colored premium paper masking tape suitable for various applications. Use it for demanding masking applications, marking, closing, bundling and many more.

### Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

### Product Features

The products' natural rubber adhesive offers high tack and excellent adhesion on a variety of surfaces. It can withstand high temperatures making it suitable for oven-drying.

### Application Fields

\*High temperature resistant masking tape, ideal for demanding masking applications during spray painting.

\*Ideal for marking, color coding, bundling and bag sealing.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                       |                     |        |
|--------------------|-----------------------|---------------------|--------|
| • Backing material | slightly-creped paper | • Bio-based content | 48 %   |
| • Type of adhesive | natural rubber        | • Total thickness   | 135 µm |

### Properties/Performance Values

- |                       |         |                                   |           |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 13 %    | • Hand tearability                | very good |
| • Tensile strength    | 33 N/cm | • Paint anchorage                 | very good |
| • Easy to remove      | yes     | • Temperature resistance (60 min) | 140 °C    |

### Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 4.8 N/cm |
|---------|----------|

# tesa<sup>®</sup> 4328

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4328PV0RD>