# tesa® Softprint 73726 Secure (SC-X)



## Product Information

Plate Mounting Tape, SC-X, Flex, 500 Medium-Hard Foam

### Product Description

tesa® Softprint 73726, a double-sided foam tape, supports with a secure and strong bonding performance to enhance printing process efficiency. The product combines our Secure (SC) plate side adhesive with a Xtra (X) strong bonding strength towards the sleeves, and is equippend with our embossed PP liner.

### Product Features

- Secure bond - excellent resistance to edge lifting across a broad temperature range
- Reliable mounting also at lower temperatures
- Works best in clean and standardized conditions

### Application Fields

Mounting of 1.14 mm (0.045") and 1.70 mm (0.067") flexographic printing plates onto steel /alu /PU and glassine sleeves.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

| | | | |
|---|---|---|---|
| • Backing | PE foam with film lamination | • Type of liner | PP |
| • Type of adhesive | tackified acrylic | • Total thickness | 550 µm |

### Properties/Performance Values

| | | | |
|---|---|---|---|
| • Color of foam | blue | • Product design | FLEX |
| • Hardness | medium-hard | • Thickness category | 500 |

### Additional Information

tesa® Softprint Secure is available in two different product designs (Classic or Flex), five different foam hardnesses (X-Soft, Soft, Medium, Medium-Hard, Hard), and with two liner options (embossed PP liner, structured Easy Application (EA) liner) to support a reliable, efficient process with the best print quality outcome.

- Flex design equipped with flexible PE reinforcement layer
- Foam properties: Long lasting, constant recovery characteristics
- Liner: white embossed PP liner

**For latest information on this product please visit http://l.tesa.com/?ip=73726**

# tesa® Softprint 73726 Secure (SC-X)

Product Information

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

**For latest information on this product please visit http://l.tesa.com/?ip=73726**