

# tesa® flameXtinct 45020

## Product Information



## Product Description

PRELIMINARY PI SHEET:

The tesa® flameXtinct product family comprises a variety of high performance adhesive tape solutions for mounting applications.

Our tesa® flameXtinct 45020 is compliant with FAR 25.853 (a) app. F part 1 and therefore fulfills the highest industry standards.

National and international regulations tend to restrict the use of certain halogenated products already and even more in the future. tesa® flameXtinct 45020 already answers this product requirement.

Due to the differential product design, repositioning is possible during installation. If necessary a fast and efficient carpet exchange is possible due to residue free removability.502

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	PET	• Total thickness	190 µm
• Type of adhesive	FR acrylic	• Colour	transparent

### Properties/Performance Values

• Elongation at break	155 %	• Hand tearability	no
• Ageing resistance (UV)	yes		

### Adhesion to Values

• Steel (initial)	4 N/cm	• Steel (covered side, after 3 days)	8 N/cm
• Steel (after 3 days)	4 N/cm		

# tesa<sup>®</sup> flameXtinct 45020

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=45020PV0FR>