

tesafilm®

Product Information

59043, 59035, 59036, 59034, 59032, 59040, 59047, 59044, 59048, 59033

Sustainable Aspects

- Tape (backing): 100% post-consumer recycled plastic (PCR PET), total tape 66% (excluding core and packaging) - validated by UL for UL2809-2 (ECVP Environmental Claim Validation Procedure)
- INGEDE-12 certified: does not harm the recycling process of paper and cardboard

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing material | PET film | • Total thickness | 39 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|---------------------|--|
| • Elongation at break | 100 % | • Solvent free | yes |
| • Tensile strength | 50 N/cm | • Suitable surfaces | Even floor, Non-woven lining paper, Glazed Tiles, Paper wallpaper, Most plastics, Glass, Cardboard, Metal, Steel, Even wood, Tiles, Acrylic glass, Paper |
| • Ageing resistance (UV) | yes | | |
| • Hand tearability | no | | |
| • Low noise unwinding | yes | | |
| • Photocopy neutral | yes | | |
| | | • Tear resistance | yes |
| | | • Transparency | good |
| | | • Unwind force n/cm | 3 N/cm |
| | | • Writable | no |

Certificates

Certified according to

- UL ECVP 2809-2
- INGEDE12

tesafilm®

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=59033A>