

tesa® Professional 4363

product



Adhesive cloth tape - 2 weeks UV-resistant

tesa® 4363 is a 2 week UV-resistant cloth tape. It consists of a PE coated 70 mesh woven PET fabric backing, coated with a pressure sensitive natural rubber adhesive.

tesa® 4363 UV is suitable for short term protection of areas like window frames, facades and other surfaces during plastering and painting at construction sites.

Features:

- 2 week UV resistance
- good adhesion, even on rough surfaces
- waterproof
- conformable
- easy to remove without residues
- easy to unwind
- available color: blue

Main Application

- Outdoor masking (up to 2 weeks)
- Protection of delicate surfaces during plastering and painting
- Protection against dirt and damage through manufacturing tools and material
- Various applications in construction and house building
- Masking of window frames and facades

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	cloth	• Tensile strength	60 N/cm
• Total thickness	310 µm	• UV-resistance	3 weeks
• Type of adhesive	natural rubber	• Mesh	65 count per square inch
• Elongation at break	11 %		

Adhesion to

- steel 3.6 N/cm

Properties

- | | | | |
|-----------------------------------|-----|-------------------------------|-----|
| • Hand tearability | ●●● | • Suitable for rough surfaces | ●●● |
| • Suitable for sensitive surfaces | ●●● | • Conformability | ●●● |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

Recommendation: please conduct a test on the application surface before using the product.

tesa® Professional 4363

product



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04363>