

tesa® Professional 4333 Precision Mask® Sensitive



Product Information

High grade washi masking tape for precise and flat paint edges on sensitive surfaces

The masking tape tesa® Precision Mask® 4333 is perfectly suited for painting work on sensitive surfaces such as wall coverings, wallpaper and varnished surfaces. As a professional masking tape it is extremely gentle yet still sticks firmly. Therefore it prevents paint tears without damaging the surface. This innovative professional masking tape comprises a tear-proof, extremely thin special backing which is coated with an acrylate adhesive compound and is particularly easy to use. This new masking tape was developed especially for applications where maximum precision is vital.

Main Application

- For masking of highly-sensitive and critical surfaces (e.g. wallcoverings, wallpapers, lacquered surfaces)
- For smooth and slightly textured surfaces
- Indoor masking

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

- | | | | |
|--------------------|------------|-----------------------|---------|
| • Backing material | flat paper | • Type of adhesive | acrylic |
| • Colour | pink | • Elongation at break | 5 % |
| • Total thickness | 80 µm | • Tensile strength | 32 N/cm |

Properties

- | | | | |
|-----------------------------------|------|---------------------|------|
| • Suitable for sensitive surfaces | ●●●● | • Paint anchorage | ●●●● |
| • Suitable for rough surfaces | ●● | • Sharp colour edge | ●●●● |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

tesa® Professional 4333 Precision Mask® Sensitive



Product Information

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04333>