

# tesa<sup>®</sup> Adhesive Nail for Wallpaper & Plaster 1kg



BNR 77773

## Product Features

- For textured and sensitive surfaces like wallpaper or plaster
- For objects up to 1kg\* per nail or 2kg using 2 nails
- Removable without a trace
- Reusable with a new strip

\*For optimal results please read instruction leaflet

## Product Description

Adhesive Nail for up to 1kg. Ideal for hanging decorative items like pictures on textured and sensitive surfaces like wallpaper or plaster.

## Application Fields

- How to apply – Step by step
1. Ensure the best possible bond by cleaning the surface of dirt and dust with a dust-free cloth.
  2. Apply the Adhesive Strip to the rougher surface. In the case of wallpaper or plaster, always first apply it to the wall, with the blue tab facing the wall. Before using, make sure that your surface is strong enough to take the weight of the object you want to attach.
  3. Press down evenly over the entire strip for at least 5 seconds and only then remove the protective foil. By pressing down like this, the flexible polymer chains are activated to form U-shaped links with the surface. It's these links that give such a secure and reliable bond, so the harder and more evenly you press, the better the bond.
  4. Now apply the tesa<sup>®</sup> Adhesive Nail by aligning it on the top edge of the strip then folding it down. Press down evenly all over the entire nail for at least 5 seconds.
  5. The tab should be left accessible behind your object or beneath the nail for easy removal.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- Holding power of strip up to 1 Kg
- Type of adhesive synthetic rubber

# tesa<sup>®</sup> Adhesive Nail for Wallpaper & Plaster 1kg

## Properties/Performance Values

• Chemical resistance	no	• Reusable	yes
• Reusable with	Adhesive Strip 1kg Wallpaper	• Temperature resistance min.	5 °C
• Residue free removal	yes	• Suitable surfaces	Wallpaper, Plaster
• Area of use	Indoor	• Oil and grease resistance	no
• Waterproof	no	• Hazard material	no
• Ozone resistance	no	• UV resistant	no
• Application temperature	15 °C	• Material	PS (polystyrene)
• Temperature resistance max.	35 °C	• Humidity resistance	no

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=NaN>