



HOW TO EASILY SPLICE WITH tesa® EASYSPLICE

8 Quick Ways to Maximize Your tesa® EasySplice Performance

Check the splitting strip for damage



The splitting strips are delicate parts of the product. Make sure the splitting strip is not damaged at the beginning of the roll before you apply tesa® EasySplice.

Don't apply tape to the full width of the roll



When you apply tesa® EasySplice, leave a gap of about one thumb's width to the edge of the roll, to avoid exposed adhesive running through the machine.

Use a squeegee




Always use a squeegee when applying tesa® EasySplice to avoid premature opening and flying snippets.

Trim the edges




To avoid damage to the web, trim the paper's edges on both sides of tesa® EasySplice to avoid air pockets underneath the unsecured edges.

Check length of flag of the expiring web




Make sure that the flag is approximately as long as the distance between the bumper/contact roller and the knife. This will help to have the best bond between two webs.

Use a wider tesa® EasySplice for high speeds



For higher machine speeds, we recommend using tesa® EasySplice in a wide width to make sure there is enough adhesive contact area for a reliable splice.

Synchronize speeds



Make sure the speeds of the new and old reel are synchronized. This is essential for a secure contact between the two reels.

Don't cover the contact adhesive



Don't cover the open contact adhesive if you use reinforcement tape or liquid glue in addition to our tesa® EasySplice. It might negatively influence the adhesive's performance.