


tesa® 88710

Product Information



Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	none	• Color of liner - inside	transparent
• Type of adhesive	acrylic	• Color of liner - outside	transparent
• Type of liner	PET	• Thickness of easy release liner	75 µm
• Color	transparent	• Thickness of tape	250 µm
• Color of liner	transparent	• Thickness of tight release liner	100 µm

Properties/Performance Values

• Ageing resistance (UV)	good	• Release of liner - outside	easy
• Haze	0.001 %	• Tack	good
• Humidity resistance	very good	• Temperature resistance long term	105 °C
• Release of liner - inside	tight	• Transmittance (380 - 780nm) >	99.5 %

Adhesion to Values

• Glass (initial)	10 N/cm
-------------------	---------

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=88710>