

tesa® 58394

Product Information



Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	none	• Color	white
• Type of adhesive	acrylic	• Color of liner	white

Product Assortment

• Available thicknesses	125 µm	• Available formats	Log roll, A4 sheet
• Available colors	white	• Available liners	paper

Properties/Performance Values

• Breakdown voltage	3.5 KV	• Temperature resistance (-40°C)	very good
• Density	1.8 g/cm ³	• Temperature resistance (125°C)	very good
• Flame retardancy	V2	• Temperature resistance short term	150 °C
• Hardness - Shore 00	60 STK	• Thermal conductivity z-direction	1.3 W/mK
• Release of liner	easy		

Adhesion to Values

• Steel (initial)	2 N/cm	• Steel (20min @ RT, 90°)	2 N/cm
-------------------	--------	---------------------------	--------

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=58394>