



# tesa® 4591

## Product Information



### tesa® 4591 Fiberglass cross filament glass tape

#### Product Description

Fibreglass tapes are narrow cloth strips with woven edges that have glass-to-resin ratio to prevent unravelling. tesa® 4591 is a general purpose bidirectional cross filament tape based on glass filaments laminated to polyester film. With its reinforced fiberglass mesh, this cross filament tape combines good longitudinal tensile strength with very low elongation, making this tape the ideal choice for heavy-duty packing and strapping applications

The synthetic rubber adhesive system operates well on a wide range of surfaces, ensuring a secure bond to various substrates, even to non-polar surfaces like PE and PP. This filament tape also exhibits excellent adhesion to a variety of corrugated and solid board surfaces.

#### Product Features

- Excellent electrical insulating properties
- Extremely strong and resistant, making it the ideal choice for warpping applications
- Tear-resistant and can easily be adhered to different surfaces such as plastic, wood, glass, metal, fiberboard.
- Effective abrasion and moisture resistance, maximizing package performance in outdoor environments.

Contact us at +91 22 4741 9200 to place an order

#### Application Fields

- Bundling and palletizing
- Heavy-duty carton sealing
- Transport securing
- Fixing
- End-tabbing

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Product Construction

- |                    |                       |                   |             |
|--------------------|-----------------------|-------------------|-------------|
| • Backing          | glassfibre / PET film | • Total thickness | 115 µm      |
| • Type of adhesive | synthetic rubber      | • Color           | transparent |

#### Properties/Performance Values

- |                       |     |                    |          |
|-----------------------|-----|--------------------|----------|
| • Elongation at break | 4 % | • Tensile strength | 250 N/cm |
|-----------------------|-----|--------------------|----------|

#### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 9.5 N/cm |
|---------|----------|

For latest information on this product please visit <http://l.tesa.com/?ip=04591>



# tesa® 4591

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04591>