

# tesa® 60432

## Product Information



## Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing	PET	• Type of adhesive	water-based acrylic
• Bio-based carbon content of liner (acc. DIN EN 16640)	90 %	• Total thickness	30 µm

### Product Assortment

• Available colors	transparent
--------------------	-------------

### Properties/Performance Values

• Elongation at break	120 %	• Printability	yes
• Tensile strength	22 N/cm	• Silent unwinding	no
• Automatic application	yes	• Suitable for deep freezing	yes
• Hand tearability	no	• Transport Information	Temperature 0-70°C
• Packaging Weight	Up to 15 kg		

### Adhesion to Values

• Steel	2.2 N/cm
---------	----------

# tesa<sup>®</sup> 60432

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60432>