

tesa® 4128

Premium surface protection tape

tesa® 4128 is a mechanical and chemical resistant PVC tape, coated with a low strength natural rubber adhesive. tesa® 4128 is tear-resistant and easy to remove.

The storage time after application should not exceed one year. tesa® 4128 can be applied outdoor for a max. duration of 3 months.

Main Application

Masking tape for wide range of masking requirements

Technical Data

▪ Backing material	PVC film	▪ Adhesion to steel	0.15 N/cm
▪ Total thickness	60 µm	▪ Elongation at break	70 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	47 N/cm

Properties

▪ Easy to remove	yes	▪ Low unwinding force	● ● ●
▪ Printability	● ● ●		
▪ Conformability	● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

Additional Information

The product design of tesa® 4128 allows convenient application by hand and is also suitable for converting and die-cutting. The best-before-date is max. 12 months under recommended storage conditions.

For latest information on this product please visit <http://l.tesa.com/?ip=04128>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.