productinformation

tesa® 4139

Single-Sided Splicing Tape

tesa® 4139 is a transparent tape with a PETP backing. Its silicone adhesive system offers excellent adhesion to ”non-stick”/ siliconized surfaces.

Colour: Transparent

Main Application

The silicone release coating on the backing of tesa® 4139 makes it ideally suited for the splicing of paper and filmic release liners. Its coating maintains the release properties of the liner materials in the splice area.
The very low thickness of tesa® 4139 makes it suitable splicing applications, for very sensitive machinery.

Technical Data

Total thickness	80 µm
Adhesion to steel	4.5 N/cm
Adhesion to silicone	3.5 N/cm
Elongation at break	40 %
Tensile strength	30 N/cm

Additional Information

The product's shelf-life is 6 months.

For latest information on this product please visit http://l.tesa.com/?ip=04139

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user’s method of application. If you are in any doubt, our technical support staff will be glad to support you.

great to work with