

## tesa® 4592

### UV, high temperature and ageing resistant mono filament tape

tesa® 4592 is a special unidirectional filament tape based on glass filaments laminated to polyester film. tesa® 4592 combines good longitudinal tensile strength with very low elongation. The tape is tear resistant.

The unique acrylic adhesive system allows the product to have:

- UV resistance
- High temperature resistance (up to 150°C short term)
- High ageing resistance

## Main Application

Transport securing, fixing, bundling, palletising and end-tapping applications which require UV, high temperature or ageing resistance. Especially suitable for outdoor applications.

## Technical Data

▪ Backing material	glassfibre / PET film	▪ Adhesion to steel	4 N/cm
▪ Total thickness	110 µm	▪ Elongation at break below	8 %
▪ Type of adhesive	acrylic	▪ Tensile strength	250 N/cm

For latest information on this product please visit <http://l.tesa.com/?ip=04592>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.