

tesa® 4982

100µm double sided transparent filmic tape

tesa® 4982 is a transparent double-sided self-adhesive tape consisting of a PET backing and a tackified acrylic adhesive.

tesa® 4982 features especially:

- Excellent bonding strength/thickness ratio
- Good bonding strength to most common, smooth, even substrates
- Reliable adhesion in high temperature applications

Main Application

- Mounting of backlight to LCD panel
- Mounting of LCD panel to metal frame
- Battery pack mounting

Technical Data

▪ Backing material	PET film	▪ Type of adhesive	tackified acrylic
▪ Color	transparent	▪ Elongation at break	50 %
▪ Total thickness	100 µm	▪ Tensile strength	20 N/cm

Adhesion to

▪ Steel (initial)	8.2 N/cm	▪ Steel (after 14 days)	11.7 N/cm
▪ ABS (initial)	7.6 N/cm	▪ ABS (after 14 days)	9.6 N/cm
▪ Aluminium (initial)	7.9 N/cm	▪ Aluminium (after 14 days)	10.6 N/cm
▪ PC (initial)	9.2 N/cm	▪ PC (after 14 days)	11.0 N/cm
▪ PE (initial)	4.6 N/cm	▪ PE (after 14 days)	5.1 N/cm
▪ PET (initial)	7.0 N/cm	▪ PET (after 14 days)	8.4 N/cm
▪ PP (initial)	4.4 N/cm	▪ PP (after 14 days)	6.2 N/cm
▪ PS (initial)	8.3 N/cm	▪ PS (after 14 days)	9.2 N/cm
▪ PVC (initial)	7.0 N/cm	▪ PVC (after 14 days)	10.0 N/cm

Properties

▪ Temperature resistance short term	200 °C	▪ Resistance to chemicals	●●●●
▪ Temperature resistance long term	100 °C	▪ Softener resistance	●●●●
▪ Tack	●●	▪ Static shear resistance at 23°C	●●●●
▪ Ageing resistance (UV)	●●●●●	▪ Static shear resistance at 40°C	●●●●
▪ Humidity resistance	●●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04982>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa® 4982

100µm double sided transparent filmic tape

Additional Information

Liner variants:

PV0 brown glassine paper (71µm; 82g/m²)

PV6 red MOPP-film (80µm; 72g/m²)

For latest information on this product please visit <http://l.tesa.com/?ip=04982>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.