

## tesa® 6910 Laser-Label Color-Change marking

tesa® 6910 is a high-performance polyolefin laser-film. Marking and cutting are achieved by laser in one step, which makes it possible to realize any desirable label variation and format using only one material. The backing is resistant against chemicals, abrasion, temperature and ageing. The adhesive system consists of a resin modified acrylic, suitable even for low energy surfaces.

This high performance product is used as a data carrier for intelligent process steering and as an identification label. Marking is achieved by laser-activated color pigments embedded in the backing. The use of a high-speed laser enables a considerably quick marking speed up to 4000mm/ sec.

Available in white color.

### Main Application

- Precise and resistant marking
- Very resistant to heat, abrasion and chemicals
- Manipulation leaves visible trace
- Flexible formatting and label design: marking and cutting by the laser
- Efficient: replaces a multitude of pre-made labels
- Just-in-time production reduces storage needs

### Technical Data

▪ Backing material	polyolefin	▪ Adhesive weight	25 g/m <sup>2</sup>
▪ Tamper Evidence	no	▪ Adhesion to Steel >	4 N/cm
▪ Peel off force from liner	0.5-10 cN/cm	▪ Type of liner	coated paper
▪ Thickness of tape	100 µm	▪ Weight of liner	120 g/m <sup>2</sup>
▪ Type of adhesive	acrylic	▪ Shelf life time	24 months

### Properties

▪ Printability	●●●●	▪ Humidity resistance	●●●●
▪ Temperature resistance short term	120 °C	▪ Resistance to chemicals	●●●
▪ Temperature resistance long term	100 °C	▪ Suitable Laser	Nd:YAG
▪ Ageing resistance (UV)	●●●	▪ Storage conditions	23°C, 50% RH, stored in original box
▪ Frost resistance	-20 °C		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=06910>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

## tesa® 6910 Laser-Label

### Color-Change marking

#### Additional Information

Standard Dimensions:

Width: 100mm and 120mm, length: 300m

For latest information on this product please visit <http://l.tesa.com/?ip=06910>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.