

tesa® ACX^{plus} 7056

ACX^{plus} High Transparency 1500µm

tesa® ACX^{plus} 7056 is a transparent acrylic core tape. It consists of a high-performance acrylic system and is primarily characterised by its Bonding Power, Stress Dissipation and its Temperature and Weather Resistance. Due to the high transparency it is especially suitable for constructive bonding of transparent and translucent materials such as glass or acrylic.

The visco-elastic, solid acrylic core compensates different thermal elongation of bonded parts.

Main Application

Bonding of transparent and translucent materials in the following Industries:

- Partition Walls
- Sign manufacturing
- Deco Glass Panels

Technical Data

▪ Backing material	solid acrylic	▪ Type of adhesive	pure acrylic
▪ Color	transparent	▪ Elongation at break	1000 %
▪ Total thickness	1500 µm		

Adhesion to

▪ Steel (initial)	17.0 N/cm	▪ Steel (after 3 days)	27.0 N/cm
▪ Aluminium (initial)	14.0 N/cm	▪ Aluminium (after 3 days)	24.0 N/cm
▪ Glass (initial)	20.0 N/cm	▪ Glass (after 3 days)	26.0 N/cm
▪ PMMA (initial)	13.0 N/cm	▪ PMMA (after 3 days)	19.0 N/cm

Properties

▪ Temperature resistance short term	200 °C	▪ Resistance to chemicals	●●●●
▪ Temperature resistance long term	100 °C	▪ Softener resistance	●●
▪ Tack	●●●	▪ Static shear resistance at 23°C	●●●●
▪ Ageing resistance (UV)	●●●●	▪ Static shear resistance at 70°C	●●●
▪ Humidity resistance	●●●●	▪ T-block	●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

PV 24 = Blue filmic liner

tesa® ACX^{plus} 7056 is recognized according to UL Standard 746C. UL File QQW2.E309290

For latest information on this product please visit <http://l.tesa.com/?ip=07056>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.